NSN 5910-01-123-0749



Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2	
View Online at https://aerobasegroup.com/nsn/5910-01-123-0749	
Body Style:	
W/mtg tabs/flanges terminals on opposite surfaces	
Reliability Indicator:	
Not established	
Body Length:	
7.400 inches	
Body Width:	
2.200 inches	
Body Height:	
2.750 inches	
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:	
8.000 inches	
Schematic Diagram Designator:	
No common or grounded electrode (s)	
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:	
1.600 inches	
Mounting Facility Screw Thread Series Designator:	
Unc	
Mounting Facility Type And Quantity:	
4 threaded mounting holes	
Features Provided:	
Hermetically sealed case	
Capacitance Value Per Section:	
120.000 microfarads single section	
Nonderated Operating Temp:	
Between -55.0 degrees celsius and 125.0 degrees celsius	
Thread Size:	
0.164 inches	
Nonderated Continuous Voltage Rating And Type Per Section:	

140.0 ac-rms single section

Tolerance Range Per Section:

-5.00/+15.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

200000.0 megohms

Dissipation Factor At Reference Tempurature In Percent:

0.1500

Terminal Type And Quantity:

2 threaded hole

Shelf Life:

N/a

NSN 5910-01-123-0749

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



	• -			
In	ıŧ	()t	Measure	•

--

Demilitarization:

No

Fiig:

A010b0