NSN 5910-01-123-1407

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-123-1407 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Established **Reliability Failure Rate Level In Percent:** 1.0000 **Terminal Length:** 2.250 inches **Body Diameter:** 0.312 inches **Body Length:** Between 0.625 inches and 0.672 inches **Terminal Diameter:** 0.025 inches **Schematic Diagram Designator:** Electrod (s) grounded to case, w/gnd terminal **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 40.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 30.0 dc single section **Tolerance Range Per Section:** -20.00/+20.00 percent single section **Case Material:** Metal **Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent:** Dc Leakage At Reference Temp: 1.000 microamperes **Case Insulation Material: Plastic Terminal Type And Quantity:** 2 uninsulated wire lead Shelf Life: N/a

Unit Of Measure:

NSN 5910-01-123-1407

Electrolytic Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0