

View Online at <https://aerobasegroup.com/nsn/5910-01-123-1532>

**Thread Class:**

2a

**Body Style:**

Piston

**Overall Length:**

0.530 inches

**Bushing Diameter:**

0.2334 inches

**Bushing Length:**

0.218 inches

**Body Length:**

0.312 inches

**Overall Diameter:**

Between 0.271 inches and 0.291 inches

**Temperature Coefficient Of Capacitance In Ppm Per Deg Celsius:**

0.0 single section

**Tolerance Of Temperature Coefficient In Ppm Per Deg Celsius:**

-15.0/+15.0 single section

**Center To Center Distance Between Terminals Parallel To Length:**

0.296 inches

**Center To Center Distance Between Terminals Parallel To Diameter:**

Between 0.209 inches and 0.229 inches

**Quality Factor At 25 Deg Celsius:**

5000.0

**Mounting Facility Screw Thread Series Designator:**

Uns

**Inclosure Type:**

Encased

**Tuning Characteristic:**

Straight line capacity single section

**Adjustment Device Torque:**

Between 1.000 inch-ounces and 5.000 inch-ounces

**Bushing Shape:**

Round

**Insulation Dc Resistance At 25 Deg Celsius:**

1000.0 gigohms

**Insulation Dc Resistance At Max Operating Temp:**

100.0 gigohms

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Thready Qty Per Inch (tpi):**

64

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Thread Size:**

0.2344 inches

**Capacitance Range In Picofarads:**

+0.8/+10.0 single section

**Nonderated Voltage Rating And Type:**

250.0 dc continuous single section

**Adjustment Device Drive Type And Quantity:**

1 slotted screw

**Precious Material And Location:**

Terminal surfaces gold

**Precious Material:**

Gold

**Terminal Type And Quantity:**

3 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A096a0