Air Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-123-2081

Thread Class:
2a
Body Style:
Piston
Overall Length:
0.639 inches
Bushing Diameter:
0.2344 inches
Bushing Length:
0.234 inches
Body Length:
0.296 inches
Overall Diameter:
Between 0.271 inches and 0.291 inches
Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius:
0.0 single section
Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:
-25.0/+25.0 single section
Quality Factor At 25 Deg Celsius:
3000.0
Mounting Facility Screw Thread Series Designator:
Mounting racinty Screw rifeau Series Designator.
Uns
Uns
Uns Inclosure Type:
Uns Inclosure Type: Encased
Uns Inclosure Type: Encased Tuning Characteristic:
Uns Inclosure Type: Encased Tuning Characteristic: Straight line capacity single section
Uns Inclosure Type: Encased Tuning Characteristic: Straight line capacity single section Adjustment Device Torque:
Uns Inclosure Type: Encased Tuning Characteristic: Straight line capacity single section Adjustment Device Torque: Between 1.000 inch-ounces and 5.000 inch-ounces
Uns Inclosure Type: Encased Tuning Characteristic: Straight line capacity single section Adjustment Device Torque: Between 1.000 inch-ounces and 5.000 inch-ounces Bushing Shape:
Uns Inclosure Type: Encased Tuning Characteristic: Straight line capacity single section Adjustment Device Torque: Between 1.000 inch-ounces and 5.000 inch-ounces Bushing Shape: Round
Uns Inclosure Type: Encased Tuning Characteristic: Straight line capacity single section Adjustment Device Torque: Between 1.000 inch-ounces and 5.000 inch-ounces Bushing Shape: Round Insulation Dc Resistance At 25 Deg Celsius:
Uns Inclosure Type: Encased Tuning Characteristic: Straight line capacity single section Adjustment Device Torque: Between 1.000 inch-ounces and 5.000 inch-ounces Bushing Shape: Round Insulation Dc Resistance At 25 Deg Celsius: 1000.0 gigohms
Uns Inclosure Type: Encased Tuning Characteristic: Straight line capacity single section Adjustment Device Torque: Between 1.000 inch-ounces and 5.000 inch-ounces Bushing Shape: Round Insulation Dc Resistance At 25 Deg Celsius: 1000.0 gigohms Insulation Dc Resistance At Max Operating Temp:
Uns Inclosure Type: Encased Tuning Characteristic: Straight line capacity single section Adjustment Device Torque: Between 1.000 inch-ounces and 5.000 inch-ounces Bushing Shape: Round Insulation Dc Resistance At 25 Deg Celsius: 1000.0 gigohms Insulation Dc Resistance At Max Operating Temp: 100.0 gigohms
Uns Inclosure Type: Encased Tuning Characteristic: Straight line capacity single section Adjustment Device Torque: Between 1.000 inch-ounces and 5.000 inch-ounces Bushing Shape: Round Insulation Dc Resistance At 25 Deg Celsius: 1000.0 gigohms Insulation Dc Resistance At Max Operating Temp: 100.0 gigohms Mounting Facility Type And Quantity:
Uns Inclosure Type: Encased Tuning Characteristic: Straight line capacity single section Adjustment Device Torque: Between 1.000 inch-ounces and 5.000 inch-ounces Bushing Shape: Round Insulation Dc Resistance At 25 Deg Celsius: 1000.0 gigohms Insulation Dc Resistance At Max Operating Temp: 100.0 gigohms Mounting Facility Type And Quantity: 1 threaded bushing
Uns Inclosure Type: Encased Tuning Characteristic: Straight line capacity single section Adjustment Device Torque: Between 1.000 inch-ounces and 5.000 inch-ounces Bushing Shape: Round Insulation Dc Resistance At 25 Deg Celsius: 1000.0 gigohms Insulation Dc Resistance At Max Operating Temp: 100.0 gigohms Mounting Facility Type And Quantity: 1 threaded bushing Thready Qty Per Inch (tpi):
Uns Inclosure Type: Encased Tuning Characteristic: Straight line capacity single section Adjustment Device Torque: Between 1.000 inch-ounces and 5.000 inch-ounces Bushing Shape: Round Insulation Dc Resistance At 25 Deg Celsius: 1000.0 gigohms Insulation Dc Resistance At Max Operating Temp: 100.0 gigohms Mounting Facility Type And Quantity: 1 threaded bushing Thready Qty Per Inch (tpi): 64

0.2344 inches



Capacitance Range In Picofarads: +1.0/+14.0 single section Nonderated Voltage Rating And Type: 250.0 dc continuous single section Adjustment Device Drive Type And Quantity: 1 slotted screw Terminal Type And Quantity: 1 tab, solder lug Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A096a0