NSN 5910-01-123-6367

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-123-6367 **Body Style:** W/thd mtg bushing, terminals on opposite ends **Reliability Indicator:** Not established Width Across Flats: 0.156 inches **Terminal Length:** 0.100 inches **Body Length:** 0.340 inches **Terminal Diameter:** 0.032 inches **Schematic Diagram Designator:** Feedthrough **Mounting Facility Screw Thread Series Designator:** Unc **Mounting Facility Type And Quantity:** 1 threaded bushing **Insulation Resistance At Maximum Operating Temp:** 2000.0 megohms **Capacitance Value Per Section:** 10.000 picofarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius **Thread Size:** 0.112 inches Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section **Tolerance Range Per Section:** -20.00/+20.00 percent single section Case Material: Metal **Insulation Resistance At Reference Temp:** 20000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 3.0000 **Terminal Surface Treatment:** Solder **Terminal Type And Quantity:**

2 uninsulated wire lead

Shelf Life:

N/a

NSN 5910-01-123-6367

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



| ш | ın | 10 | <i>(</i>)+ | Measure: | |
|---|----|----|-------------|----------|--|
| | | | | | |

--

Demilitarization:

No

Fiig:

A010b0