

View Online at https://aerobasegroup.com/nsn/5910-01-123-6368

#### **Body Style:**

W/thd mtg bushing, terminals on opposite ends

**Reliability Indicator:** 

Not established

## Width Across Flats:

0.156 inches

#### **Terminal Length:**

0.100 inches

#### **Body Length:**

0.340 inches

### **Terminal Diameter:**

0.032 inches

#### Schematic Diagram Designator:

Feedthrough

### Mounting Facility Screw Thread Series Designator:

Unc

## Mounting Facility Type And Quantity:

1 threaded bushing

### Insulation Resistance At Maximum Operating Temp:

2000.0 megohms

#### **Capacitance Value Per Section:**

500.000 picofarads single section

#### Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

### Thread Size:

0.112 inches

## Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

#### **Tolerance Range Per Section:**

-20.00/+80.00 percent single section

#### Case Material:

Metal

# Insulation Resistance At Reference Temp:

20000.0 megohms

# Dissipation Factor At Reference Tempurature In Percent:

3.0000

# **Terminal Surface Treatment:**

Solder

# Terminal Type And Quantity:

2 uninsulated wire lead

## Shelf Life:

N/a



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0