## NSN 5910-01-123-8480

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-123-8480

Body Style:
W/o mtg facilities, terminals on opposite surfaces
Reliability Indicator:
Not established
Terminal Length:
1.500 inches
Body Length:
0.900 inches
Body Width:
0.380 inches
Body Height:
0.500 inches
Terminal Diameter:
0.027 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
2.700 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 100.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section
50.0 dc single section
50.0 dc single section  Tolerance Range Per Section:
50.0 dc single section  Tolerance Range Per Section: -20.00/+20.00 percent single section
50.0 dc single section  Tolerance Range Per Section: -20.00/+20.00 percent single section  Case Material:
50.0 dc single section  Tolerance Range Per Section: -20.00/+20.00 percent single section  Case Material: Plastic
50.0 dc single section  Tolerance Range Per Section: -20.00/+20.00 percent single section  Case Material: Plastic  Dissipation Factor At Reference Tempurature In Percent:
50.0 dc single section  Tolerance Range Per Section: -20.00/+20.00 percent single section  Case Material: Plastic  Dissipation Factor At Reference Tempurature In Percent: 1.0000
50.0 dc single section  Tolerance Range Per Section: -20.00/+20.00 percent single section  Case Material: Plastic  Dissipation Factor At Reference Tempurature In Percent: 1.0000  Terminal Surface Treatment:
50.0 dc single section  Tolerance Range Per Section: -20.00/+20.00 percent single section  Case Material: Plastic  Dissipation Factor At Reference Tempurature In Percent: 1.0000  Terminal Surface Treatment: Solder
50.0 dc single section  Tolerance Range Per Section: -20.00/+20.00 percent single section  Case Material: Plastic  Dissipation Factor At Reference Tempurature In Percent: 1.0000  Terminal Surface Treatment: Solder  Terminal Type And Quantity:
50.0 dc single section  Tolerance Range Per Section: -20.00/+20.00 percent single section  Case Material: Plastic  Dissipation Factor At Reference Tempurature In Percent: 1.0000  Terminal Surface Treatment: Solder  Terminal Type And Quantity: 2 uninsulated wire lead
50.0 dc single section  Tolerance Range Per Section: -20.00/+20.00 percent single section  Case Material: Plastic  Dissipation Factor At Reference Tempurature In Percent: 1.0000  Terminal Surface Treatment: Solder  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life:
50.0 dc single section  Tolerance Range Per Section: -20.00/+20.00 percent single section  Case Material: Plastic  Dissipation Factor At Reference Tempurature In Percent: 1.0000  Terminal Surface Treatment: Solder  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a
50.0 dc single section  Tolerance Range Per Section: -20.00/+20.00 percent single section  Case Material: Plastic  Dissipation Factor At Reference Tempurature In Percent: 1.0000  Terminal Surface Treatment: Solder  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a
Tolerance Range Per Section: -20.00/+20.00 percent single section  Case Material: Plastic  Dissipation Factor At Reference Tempurature In Percent: 1.0000  Terminal Surface Treatment: Solder  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a  Unit Of Measure:
Tolerance Range Per Section: -20.00/+20.00 percent single section  Case Material: Plastic  Dissipation Factor At Reference Tempurature In Percent: 1.0000  Terminal Surface Treatment: Solder  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a  Unit Of Measure:  Demilitarization: