NSN 5910-01-124-2434

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-124-2434 **Body Style:** W/o mtg facilities, terminal (s) on one end Reliability Indicator: Not established **Terminal Length:** 0.188 inches **Body Diameter:** 1.391 inches **Body Length:** 4.172 inches **Center To Center Distance Between Terminals Parallel To Diameter:** 0.500 inches **Terminal Diameter:** 0.190 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Plain foil **Impedance At Minimum Operating Tempurature In Ohms:** 120.0 **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 25000.000 microfarads single section **Nonderated Operating Temp:** Between -40.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 15.0 dc single section **Tolerance Range Per Section:** -10.00/+75.00 percent single section **Equivalent Series Resistance At Reference Tempurature In Ohms:**

Case Material: Metal **Capacitive Electrode Material:** Aluminum Dc Leakage At Reference Temp: 3.670 milliamperes **Terminal Surface Treatment:** Solder **Case Insulation Material: Plastic**

NSN 5910-01-124-2434

Electrolytic Fixed Capacitor - Page 2 of 2



Terminal	Type	And	Quantity:
----------	------	-----	-----------

2 threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0