## NSN 5910-01-125-2003

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-125-2003

view Online at https://aerobasegroup.com/nsi/5910-01-125-2003
Body Style:
W/o mtg facilities terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
Between 1.000 inches and 1.500 inches
Body Diameter:
0.450 inches
Body Length:
0.450 inches
Body Width:
0.470 inches
Body Height:
0.295 inches
Center To Center Distance Between Terminals Parallel To Length:
0.250 inches
Terminal Diameter:
0.020 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Electrical Polarization:
Polarized
Capacitance Value Per Section:
100.000 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Dc Leakage At Maximum Operating Temp:
0.2 microamperes
Nonderated Continuous Voltage Rating And Type Per Section:
6.0 dc single section
Tolerance Range Per Section:
-20.00/+20.00 percent single section
Case Material:
Plastic
Capacitive Electrode Material:
Tantalum
Dc Leakage At Reference Temp:
0.020 microamperes
Terminal Surface Treatment:

Solder

**Terminal Type And Quantity:** 

2 uninsulated wire lead

## NSN 5910-01-125-2003

Electrolytic Fixed Capacitor - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0