

View Online at <https://aerobasegroup.com/nsn/5910-01-126-2054>

**Body Style:**

W/o mtg facilities, terminals on opposite surfaces

**Reliability Indicator:**

Established

**Reliability Failure Rate Level In Percent:**

1.0000

**Terminal Length:**

0.250 inches

**Body Length:**

0.135 inches

**Body Width:**

Between 0.060 inches and 0.100 inches

**Body Height:**

0.115 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Insulation Resistance At Maximum Operating Temp:**

100000.0 megohms

**Capacitance Value Per Section:**

15.000 picofarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Temperature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:**

90.0 single section

**Nonderated Continuous Voltage Rating And Type Per Section:**

500.0 dc single section

**Tolerance Of Temperature Coefficient Per Section In Ppm Per Deg Celsius:**

-20.0/+20.0 single section

**Tolerance Range Per Section:**

-1.00/+1.00 percent single section

**Case Material:**

Ceramic or glass

**Insulation Resistance At Reference Temp:**

1000000.0 megohms

**Dissipation Factor At Reference Temperature In Percent:**

0.0500

**Quality Factor At Reference Temp:**

10000.0000

**Terminal Surface Treatment:**

Silver

**Precious Material And Location:**

Terminal surfaces silver

**Test Data Document:**

81349-mil-c-55681 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 ribbon

**Specification Data:**

81349-mil-c-55681/5 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A010b0