## NSN 5910-01-126-2339

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-126-2339

**Body Style:** 

W/mtg bracket, axial terminals

**Reliability Indicator:** 

Not established

**Terminal Length:** 

Between 1.625 inches and 2.625 inches

**Body Diameter:** 

Between 0.495 inches and 0.505 inches

**Body Length:** 

Between 0.844 inches and 0.906 inches

**Terminal Diameter:** 

0.025 inches

**Unthreaded Mounting Hole Diameter:** 

Between 0.151 inches and 0.161 inches

**Schematic Diagram Designator:** 

Electrod (s) grounded to case, w/gnd terminal

**Mounting Facility Type And Quantity:** 

1 unthreaded mounting holes

**Features Provided:** 

Hermetically sealed case

**Insulation Resistance At Maximum Operating Temp:** 

6000.0 megohm-microfarads

**Capacitance Value Per Section:** 

0.680 microfarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 105.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

150.0 ac-rms single section

**Tolerance Range Per Section:** 

-10.00/+10.00 percent single section

**Case Material:** 

Metal

**Insulation Resistance At Reference Temp:** 

25000.0 megohm-microfarads

**Dissipation Factor At Reference Tempurature In Percent:** 

0.180

**Terminal Surface Treatment:** 

Solder

**Dielectric Material:** 

Plastic polycarbonate

**Case Insulation Material:** 

**Plastic** 

## NSN 5910-01-126-2339

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Terminal Type And Quantity:
2 uninsulated wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A010b0