## NSN 5910-01-126-2508

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-126-2508

**Body Style:** 

W/o mtg facilities, axial terminals

**Reliability Indicator:** 

Not established

**Terminal Length:** 

Between 0.234 inches and 0.358 inches

**Body Diameter:** 

Between 0.745 inches and 0.765 inches

**Body Length:** 

Between 2.094 inches and 2.156 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Features Provided:** 

Hermetically sealed case

**Insulation Resistance At Maximum Operating Temp:** 

10000.0 megohms

**Capacitance Value Per Section:** 

1.000 microfarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

330.0 ac-rms single section

**Tolerance Range Per Section:** 

-10.00/+10.00 percent single section

**Case Material:** 

Metal

**Insulation Resistance At Reference Temp:** 

50000.0 megohms

**Dissipation Factor At Reference Tempurature In Percent:** 

0.300

**Terminal Surface Treatment:** 

Solder

**Dielectric Material:** 

Plastic polycarbonate

**Case Insulation Material:** 

Plastic

**Terminal Type And Quantity:** 

2 uninsulated wire lead w/terminal lug

**Specification Data:** 

57057-8814600005-3 manufacturers specification control

Shelf Life:

N/a

## NSN 5910-01-126-2508

Plastic Dielectric Fixed Capacitor - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0