

View Online at https://aerobasegroup.com/nsn/5910-01-126-2508

### **Body Style:**

W/o mtg facilities, axial terminals

**Reliability Indicator:** 

Not established

### Terminal Length:

Between 0.234 inches and 0.358 inches

#### **Body Diameter:**

Between 0.745 inches and 0.765 inches

#### **Body Length:**

Between 2.094 inches and 2.156 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

### Features Provided:

Hermetically sealed case

#### Insulation Resistance At Maximum Operating Temp:

10000.0 megohms

### Capacitance Value Per Section:

1.000 microfarads single section

### Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

### Nonderated Continuous Voltage Rating And Type Per Section:

330.0 ac-rms single section

### **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

#### **Case Material:**

Metal

#### Insulation Resistance At Reference Temp:

50000.0 megohms

# Dissipation Factor At Reference Tempurature In Percent:

0.300

# **Terminal Surface Treatment:**

Solder

# **Dielectric Material:**

Plastic polycarbonate

# Case Insulation Material:

Plastic

# Terminal Type And Quantity:

2 uninsulated wire lead w/terminal lug

# **Specification Data:**

57057-8814600005-3 manufacturers specification control

### Shelf Life:

N/a

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0