Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-127-2952

## **Body Style:**

W/o mtg facilities, radial terminals

**Reliability Indicator:** 

Not established

# **Terminal Length:**

1.250 inches

### **Body Diameter:**

0.450 inches

#### **Body Length:**

0.750 inches

### Center To Center Distance Between Terminals Parallel To Length:

0.375 inches

**Terminal Diameter:** 

0.032 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

# Internal Electrical Connection Type:

Extended foil

## Insulation Resistance At Maximum Operating Temp:

2500.0 megohm-microfarads

## Capacitance Value Per Section:

4700.000 picofarads single section

#### Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

600.0 dc single section

#### **Tolerance Range Per Section:**

-5.00/+5.00 percent single section

#### **Case Material:**

Plastic

#### Insulation Resistance At Reference Temp:

50000.0 megohm-microfarads

## **Dissipation Factor At Reference Tempurature In Percent:**

0.1000

## **Terminal Surface Treatment:**

Solder

#### **Terminal Type And Quantity:**

2 uninsulated wire lead

Shelf Life:

N/a

#### Unit Of Measure:

---

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0