NSN 5910-01-127-6348

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-127-6348

Body Style:
W/o mtg facilities terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
0.393 inches
Body Length:
0.570 inches
Body Width:
0.750 inches
Body Height:
0.200 inches
Center To Center Distance Between Terminals Parallel To Length:
0.400 inches
Terminal Diameter:
0.025 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
0.047 microfarads single section
Nonderstad Operation Towns
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Between -55.0 degrees celsius and 85.0 degrees celsius
Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section:
Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section
Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section:
Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section
Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material:
Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Plastic
Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 5000.0 megohms
Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 5000.0 megohms Dissipation Factor At Reference Tempurature In Percent:
Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 5000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 1.0000
Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 5000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 1.0000 Terminal Surface Treatment:
Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 5000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 1.0000 Terminal Surface Treatment: Solder
Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 5000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 1.0000 Terminal Surface Treatment: Solder Terminal Type And Quantity:
Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 5000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 1.0000 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead
Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 5000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 1.0000 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life:
Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 5000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 1.0000 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a

No

NSN 5910-01-127-6348

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Fiig:

A010b0