

View Online at <https://aerobasegroup.com/nsn/5910-01-128-3551>

Body Style:

W/o mtg facilities, axial terminals

Reliability Indicator:

Not established

Terminal Length:

0.250 inches

Body Diameter:

0.130 inches

Body Length:

0.110 inches

Terminal Diameter:

0.030 inches

Schematic Diagram Designator:

Feedthrough

End Application:

Landing craft air cushion (lca); helicopter, uscg search and rescue, hh-60j; helicopter, search and rescue, hh-60h; nimitz class cvn; forrestal class cv; helicopter, carrier based asw, sh-60f; helicopter, mh-53e; helicopter, advance attack, ah-1w; wasp class lhd; milstar system

Capacitance Value Per Section:

100.000 picofarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

0.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-30.0/+30.0 single section

Criticality Code Justification:

Feat

Tolerance Range Per Section:

-20.00/+20.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

500.0 megohms

Power Factor At Reference Tempurature In Percent:

3.5000

Special Features:

Weapon system essential

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0