

View Online at https://aerobasegroup.com/nsn/5910-01-128-3557

### **Body Style:**

W/thd bushing mtg, terminals on opposite end

**Reliability Indicator:** 

Not established

### Width Across Flats:

0.187 inches

#### **Terminal Length:**

0.843 inches

#### **Body Length:**

0.359 inches

### **Terminal Diameter:**

0.032 inches

### Schematic Diagram Designator:

### Feedthrough

### Mounting Facility Screw Thread Series Designator:

Unc

# Mounting Facility Type And Quantity:

1 threaded bushing

### **Capacitance Value Per Section:**

0.050 microfarads single section

### Voltage Tempurature Limits Per Section In Percent Capacitance Change:

-20.0/+20.0 without voltage applied single section

### Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

### Thread Size:

0.164 inches

### Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

### **Tolerance Range Per Section:**

-0.00/+100.00 percent single section

### Case Material:

Metal

# Insulation Resistance At Reference Temp:

500.0 megohms

# Dissipation Factor At Reference Tempurature In Percent:

2.5000

# **Terminal Surface Treatment:**

Solder

# Terminal Type And Quantity:

2 uninsulated wire lead

### Shelf Life:

N/a



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0