

View Online at <https://aerobasegroup.com/nsn/5910-01-128-9987>

**Body Style:**

W/thd hol (s)/stud(s), terminal(s) on one surface

**Reliability Indicator:**

Not established

**Body Length:**

4.560 inches

**Body Width:**

1.900 inches

**Body Height:**

2.970 inches

**Center To Center Distance Between Terminals Parallel To Length:**

2.500 inches

**Terminal Height From Body:**

0.718 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

2.400 inches

**Schematic Diagram Designator:**

Series connected

**Anode Type:**

Plain foil

**Impedance At Minimum Operating Temperature In Ohms:**

14.0

**Electrical Polarization:**

Polarized

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.400 inches

**Mounting Facility Screw Thread Series Designator:**

Unc

**Mounting Facility Type And Quantity:**

4 threaded mounting holes

**Section Quantity:**

2

**Capacitance Value Per Section:**

360.000 microfarads all sections

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Thread Size:**

0.138 inches

**Dc Leakage At Maximum Operating Temp:**

1728.0 microamperes

**Nonderated Continuous Voltage Rating And Type Per Section:**

300.0 dc all sections

**Tolerance Range Per Section:**

-10.00/+50.00 percent all sections

**Case Material:**

Metal

**Capacitive Electrode Material:**

Aluminum

**Equivalent Series Resistance At Reference Temperature In Ohms:**

0.21

**Dc Leakage At Reference Temp:**

288.000 microamperes

**Terminal Surface Treatment:**

Solder

**Terminal Type And Quantity:**

2 standoff, solder lug and 3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A010b0