

View Online at <https://aerobasegroup.com/nsn/5910-01-128-9987>

Body Style:

W/thd hol (s)/stud(s), terminal(s) on one surface

Reliability Indicator:

Not established

Body Length:

4.560 inches

Body Width:

1.900 inches

Body Height:

2.970 inches

Center To Center Distance Between Terminals Parallel To Length:

2.500 inches

Terminal Height From Body:

0.718 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

2.400 inches

Schematic Diagram Designator:

Series connected

Anode Type:

Plain foil

Impedance At Minimum Operating Temperature In Ohms:

14.0

Electrical Polarization:

Polarized

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.400 inches

Mounting Facility Screw Thread Series Designator:

Unc

Mounting Facility Type And Quantity:

4 threaded mounting holes

Section Quantity:

2

Capacitance Value Per Section:

360.000 microfarads all sections

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Thread Size:

0.138 inches

Dc Leakage At Maximum Operating Temp:

1728.0 microamperes

Nonderated Continuous Voltage Rating And Type Per Section:

300.0 dc all sections

Tolerance Range Per Section:

-10.00/+50.00 percent all sections

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Equivalent Series Resistance At Reference Temperature In Ohms:

0.21

Dc Leakage At Reference Temp:

288.000 microamperes

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

2 standoff, solder lug and 3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A010b0