NSN 5910-01-129-4162



Ceramic Dielectric Variable Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-01-129-4162 **Body Style:** Compression **Terminal Length:** 0.125 inches **Body Length:** 0.200 inches **Body Width:** 0.200 inches **Body Height:** 0.060 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: -1100.0 single section **Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:** -300.0/+300.0 single section **Quality Factor At 25 Deg Celsius:** 200.0 **Terminal Width:** 0.040 inches **Terminal Thickness:** 0.005 inches **Inclosure Type: Encased Adjustment Device Torque:** Between 0.200 inch-ounces and 2.000 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 10000.0 megohms **Mounting Facility Type And Quantity:** 2 terminal **Nonderated Operating Temp:** Between -20.0 degrees celsius and 85.0 degrees celsius Capacitance Range In Picofarads: +7.0/+40.0 single section **Nonderated Voltage Rating And Type:** 250.0 dc continuous single section **Adjustment Device Drive Type And Quantity:** 1 square hole Capacitance Drift In Picofarads: 0.50 single section **Terminal Type And Quantity:** 2 tab, solder lug

Shelf Life: N/a

NSN 5910-01-129-4162

Ceramic Dielectric Variable Capacitor - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A096a0