Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-130-3890

Body Style:

W/o mtg facilities, axial terminals

Reliability Indicator:

Not established

Terminal Length:

1.000 inches

Body Diameter:

1.010 inches

Body Length:

1.640 inches

Center To Center Distance Between Terminals Parallel To Diameter:

0.400 inches

Terminal Diameter:

0.040 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Impedance At Minimum Operating Tempurature In Ohms:

0.03

Electrical Polarization:

Polarized

Capacitance Value Per Section:

2200.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 105.0 degrees celsius

Dc Leakage At Maximum Operating Temp:

524.0 microamperes

Nonderated Continuous Voltage Rating And Type Per Section:

20.0 dc single section

Tolerance Range Per Section:

-10.00/+100.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Equivalent Series Resistance At Reference Tempurature In Ohms:

0.051

Dc Leakage At Reference Temp:

104.000 microamperes

Terminal Surface Treatment:

Solder

Case Insulation Material:

Plastic

NSN 5910-01-130-3890

Electrolytic Fixed Capacitor - Page 2 of 2



Special Features:

One dummy wire lead terminal on opposite end

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0