

View Online at <https://aerobasegroup.com/nsn/5910-01-131-6743>

**Body Style:**

W/o mtg facilities terminal (s) on one surface

**Reliability Indicator:**

Established

**Reliability Failure Rate Level In Percent:**

0.1000

**Terminal Length:**

1.250 inches

**Body Length:**

0.190 inches

**Body Width:**

0.190 inches

**Body Height:**

0.090 inches

**Center To Center Distance Between Terminals Parallel To Length:**

0.200 inches

**Terminal Diameter:**

0.025 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Capacitance Value Per Section:**

68.000 picofarads single section

**Voltage Temperature Limits Per Section In Percent Capacitance Change:**

-25.0/+15.0 with rated voltage applied single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

200.0 dc single section

**Tolerance Range Per Section:**

-10.00/+10.00 percent single section

**Case Material:**

Plastic

**Insulation Resistance At Reference Temp:**

100000.0 megohms

**Dissipation Factor At Reference Temperature In Percent:**

2.5000

**Test Data Document:**

81349-mil-c-39014/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0