NSN 5910-01-132-1396

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-132-1396 **Body Style:** W/thd bushing mtg, terminals on opposite ends Reliability Indicator: Not established **Terminal Length:** 0.150 inches **Body Diameter:** 0.375 inches **Body Length:** 0.410 inches **Continuous Current Rating In Amps:** 15.0 **Schematic Diagram Designator:** Feedthrough **Mounting Facility Screw Thread Series Designator:** Unf **Mounting Facility Type And Quantity:** 1 threaded bushing **Features Provided:** Mounting hardware **Capacitance Value Per Section:** 0.500 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius **Thread Size:** 0.250 inches Nonderated Continuous Voltage Rating And Type Per Section: 150.0 dc single section **Tolerance Range Per Section:** -0.00/+100.00 percent single section **Thread Tolerance Class:** 2a external **Case Material:** Metal **Insulation Resistance At Reference Temp:** 1000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 4.000 **Terminal Surface Treatment:**

Solder

Terminal Type And Quantity:

2 tab, solder lug

NSN 5910-01-132-1396

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0