NSN 5910-01-132-6517



Ceramic Dielectric Fixed Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-01-132-6517 **Body Style:** W/o mtg facilities, terminals on opposite surfaces **Reliability Indicator:** Established **Reliability Failure Rate Level In Percent:** 0.1000 **Terminal Length:** 0.148 inches **Body Length:** 0.260 inches **Body Width:** Between 0.090 inches and 0.092 inches **Body Height:** 0.128 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Capacitance Value Per Section:** 10000.000 picofarads single section Voltage Tempurature Limits Per Section In Percent Capacitance Change: -25.0/+15.0 with rated voltage applied single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section Case Material: **Plastic Insulation Resistance At Reference Temp:** 100000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 2.5000 **Test Data Document:** 81349-mil-c-39014/22 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal	Type A	And C	luantity:
----------	--------	-------	-----------

2 ribbon

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5910-01-132-6517

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Fiig:

A010b0