## NSN 5910-01-132-6840

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-132-6840

view Offiline at https://aerobasegroup.com/hsh/ss/10-01-132-00-0
Body Style:
W/o mtg facilities, axial terminals
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
0.1000
Terminal Length:
1.250 inches
Body Diameter:
0.090 inches
Body Length:
0.160 inches
Terminal Diameter:
0.019 inches
Schematic Diagram Designator:
Electrod (s) grounded to case
Capacitance Value Per Section:
27.000 picofarads single section
Voltage Tempurature Limits Per Section In Percent Capacitance Change:
-25.0/+15.0 with rated voltage applied single section
Nonderated Operating Temp:
Between 55.0 degrees celsius and 125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
100.0 dc single section
Tolerance Range Per Section:
-10.00/+10.00 percent single section
Case Material:
Plastic
Insulation Resistance At Reference Temp:
100000.0 megohms
Dissipation Factor At Reference Tempurature In Percent:
2.5000
Test Data Document:
81349-mil-c-39014/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
2 uninsulated wire lead
Shelf Life:
N/a
Unit Of Measure:

No

Demilitarization:

## NSN 5910-01-132-6840

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Fiig:

A010b0