## NSN 5910-01-132-8017

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-132-8017
Body Style:
W/o mtg facilities, terminals on opposite surfaces
Reliability Indicator:
Not established
Terminal Length:
1.625 inches
Body Length:
1.500 inches
Body Width:
Between 0.407 inches and 0.499 inches
Body Height:
Between 0.703 inches and 0.827 inches
Terminal Diameter:
0.032 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
3.000 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 0.0 single section
0.0 single section
0.0 single section  Nonderated Continuous Voltage Rating And Type Per Section:
0.0 single section  Nonderated Continuous Voltage Rating And Type Per Section:  200.0 dc single section
0.0 single section  Nonderated Continuous Voltage Rating And Type Per Section:  200.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:
0.0 single section  Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section
0.0 single section  Nonderated Continuous Voltage Rating And Type Per Section:  200.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:  -30.0/+30.0 single section  Tolerance Range Per Section:
0.0 single section  Nonderated Continuous Voltage Rating And Type Per Section:  200.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:  -30.0/+30.0 single section  Tolerance Range Per Section:  -20.00/+20.00 percent single section
0.0 single section  Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section  Tolerance Range Per Section: -20.00/+20.00 percent single section  Case Material:
0.0 single section  Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section  Tolerance Range Per Section: -20.00/+20.00 percent single section  Case Material: Plastic
0.0 single section  Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section  Tolerance Range Per Section: -20.00/+20.00 percent single section  Case Material: Plastic  Insulation Resistance At Reference Temp:
0.0 single section  Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section  Tolerance Range Per Section: -20.00/+20.00 percent single section  Case Material: Plastic  Insulation Resistance At Reference Temp: 10000.0 megohms
0.0 single section  Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section  Tolerance Range Per Section: -20.00/+20.00 percent single section  Case Material: Plastic  Insulation Resistance At Reference Temp: 10000.0 megohms  Terminal Surface Treatment:
0.0 single section  Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section  Tolerance Range Per Section: -20.00/+20.00 percent single section  Case Material: Plastic Insulation Resistance At Reference Temp: 10000.0 megohms  Terminal Surface Treatment: Solder
0.0 single section  Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section  Tolerance Range Per Section: -20.00/+20.00 percent single section  Case Material: Plastic Insulation Resistance At Reference Temp: 10000.0 megohms  Terminal Surface Treatment: Solder  Terminal Type And Quantity:
Nonderated Continuous Voltage Rating And Type Per Section:  200.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:  -30.0/+30.0 single section  Tolerance Range Per Section:  -20.00/+20.00 percent single section  Case Material:  Plastic  Insulation Resistance At Reference Temp:  10000.0 megohms  Terminal Surface Treatment:  Solder  Terminal Type And Quantity:  2 uninsulated wire lead

Demilitarization:

No

## NSN 5910-01-132-8017

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Fiig:

A010b0