## NSN 5910-01-133-5494

**Body Style:** 

Ceramic Dielectric Variable Capacitor - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5910-01-133-5494



Rotary **Terminal Length:** 0.150 inches **Body Diameter:** 0.270 inches **Body Height:** 0.100 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: -400.0 single section **Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:** -500.0/+500.0 single section **Center To Center Distance Between Terminals Parallel To Diameter:** 0.220 inches **Center To Center Distance Between Mounting Facilities Parallel To Diameter:** 0.220 inches **Quality Factor At 25 Deg Celsius:** 1000.0 **Terminal Width:** 0.040 inches **Terminal Thickness:** 0.005 inches **Inclosure Type:** Encased **Adjustment Device Torque:** Between 0.200 inch-ounces and 2.000 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 10000.0 megohms **Mounting Facility Type And Quantity:** 2 terminal **Nonderated Operating Temp:** Between -20.0 degrees celsius and 85.0 degrees celsius Capacitance Range In Picofarads: +5.0/+25.0 single section **Nonderated Voltage Rating And Type:** 250.0 dc continuous single section **Adjustment Device Drive Type And Quantity:** 1 square hole **Terminal Type And Quantity:** 2 printed circuit Shelf Life: N/a

## NSN 5910-01-133-5494

Ceramic Dielectric Variable Capacitor - Page 2 of 2



| ш | ın | 10 | <i>(</i> )+ | Measure: |  |
|---|----|----|-------------|----------|--|
|   |    |    |             |          |  |

--

Demilitarization:

No

Fiig:

A096a0