

View Online at <https://aerobasegroup.com/nsn/5910-01-134-1157>

Body Style:

Rotary

Body Diameter:

0.137 inches

Body Height:

0.177 inches

Temperature Coefficient Of Capacitance In Ppm Per Deg Celsius:

-470.0 single section

Tolerance Of Temperature Coefficient In Ppm Per Deg Celsius:

-50.0/+50.0 single section

Quality Factor At 25 Deg Celsius:

500.0

End Application:

Ticonderoga class c (47), spruance class dd(963), nimitz class cvn, tarawa class lha, kidd class ddg, forrestal class cv, wasp class lhd, support equipment for b-1 aircraft, general purpose electronic test equipment, mine countermeasures support(mcs)class(lph-12)

Inclosure Type:

Encased

Adjustment Device Torque:

Between 50.000 centimeter-grams and 150.000 centimeter-grams

Mounting Facility Type And Quantity:

2 terminal

Nonderated Operating Temp:

Between -40.0 degrees celsius and 85.0 degrees celsius

Capacitance Range In Picofarads:

+3.5/+10.0 single section

Nonderated Voltage Rating And Type:

63.0 dc continuous single section

Adjustment Device Drive Type And Quantity:

1 slotted screw

Terminal Type And Quantity:

2 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0