NSN 5910-01-134-5102



Plastic Dielectric Fixed Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-01-134-5102 **Body Style:** W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Not established **Terminal Length:** 0.196 inches **Body Length:** 0.532 inches **Body Width:** 0.493 inches **Body Height:** 0.197 inches Center To Center Distance Between Terminals Parallel To Length: 0.375 inches **Terminal Diameter:** 0.010 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Insulation Resistance At Maximum Operating Temp:** 1500.0 megohms **Capacitance Value Per Section:** 5600.000 picofarads single section **Nonderated Operating Temp:** Between -40.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 125.0 ac-rms single section and 400.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section **Case Material: Plastic Insulation Resistance At Reference Temp:** 50000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 0.6000 **Terminal Surface Treatment:** Solder **Dielectric Material:** Plastic polyester **Special Features:**

Crimped leads **Terminal Type And Quantity:**

2 uninsulated wire lead

NSN 5910-01-134-5102

Plastic Dielectric Fixed Capacitor - Page 2 of 2



| Shelf | Life: |
|-------|-------|
|-------|-------|

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0