

NSN 5910-01-135-0568 Ceramic Dielectric Variable Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-01-135-0568 **Body Style:** Rotary **Terminal Length:** 0.125 inches **Overall Height:** 0.215 inches **Overall Diameter:** 0.225 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: -1400.0 single section **Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:** -700.0/+700.0 single section **Center To Center Distance Between Terminals Parallel To Diameter:** 0.200 inches **Center To Center Distance Between Mounting Facilities Parallel To Diameter:** 0.200 inches **Quality Factor At 25 Deg Celsius:** 200.0 **Terminal Width:** 0.040 inches **Terminal Thickness:** 0.008 inches **Inclosure Type:** Encased **Adjustment Device Torque:** Between 0.200 inch-ounces and 2.000 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 10000.0 megohms **Mounting Facility Type And Quantity:**

2 terminal

Nonderated Operating Temp:

Between -20.0 degrees celsius and 85.0 degrees celsius

Capacitance Range In Picofarads:

+5.0/+25.0 single section

Nonderated Voltage Rating And Type:

250.0 dc continuous single section

Adjustment Device Drive Type And Quantity:

1 slotted screw

Terminal Type And Quantity:

2 printed circuit

Shelf Life:

N/a

NSN 5910-01-135-0568

Ceramic Dielectric Variable Capacitor - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A096a0