# NSN 5910-01-135-5404

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-135-5404

# **Body Style:**

W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals

#### **Reliability Indicator:**

Not establishednot established

# **Terminal Length:**

1.500 inches 1.500 inches

#### **Body Diameter:**

Between 0.299 inches and 0.324 inches

#### **Body Length:**

Between 1.319 inches and 1.381 inches

#### **Terminal Diameter:**

Between 0.024 inches and 0.026 inches

#### **Schematic Diagram Designator:**

No common or grounded electrode (s)

#### **Anode Type:**

Solid

#### **Electrical Polarization:**

Nonpolarized

# **Features Provided:**

Hermetically sealed case

# **Capacitance Value Per Section:**

11.000 microfarads single section

#### **Nonderated Operating Temp:**

Between -80.0 degrees celsius and 85.0 degrees celsius

# Nonderated Continuous Voltage Rating And Type Per Section:

20.0 dc single section

# **Tolerance Range Per Section:**

-20.00/+20.00 percent single section

#### Case Material:

Metal

# **Capacitive Electrode Material:**

Tantalum

# **Dissipation Factor At Reference Tempurature In Percent:**

6.0000

# Dc Leakage At Reference Temp:

4.000 microamperes

#### **Terminal Surface Treatment:**

Solder

# **Case Insulation Material:**

Plastic

# **Terminal Type And Quantity:**

2 uninsulated wire lead

# NSN 5910-01-135-5404

Electrolytic Fixed Capacitor - Page 2 of 2



				-
C I	20	lŧ.	l i	fe:
J.	16		_,	ıc.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0