

View Online at <https://aerobasegroup.com/nsn/5910-01-135-6555>

Thread Class:

2a

Body Style:

Piston

Overall Length:

Between 0.448 inches and 0.520 inches

Terminal Length:

0.225 inches

Bushing Diameter:

0.234 inches

Bushing Length:

0.188 inches

Body Length:

Between 0.268 inches and 0.308 inches

Overall Diameter:

0.281 inches

Temperature Coefficient Of Capacitance In Ppm Per Deg Celsius:

0.0 single section

Tolerance Of Temperature Coefficient In Ppm Per Deg Celsius:

-50.0/+50.0 single section

Quality Factor At 25 Deg Celsius:

2000.0

Fragility Factor:

Moderately rugged

Terminal Width:

0.094 inches

Mounting Facility Screw Thread Series Designator:

Uns

Inclosure Type:

Encased

Adjustment Device Torque:

Between 0.500 inch-ounces and 6.000 inch-ounces

Bushing Shape:

Round

Insulation Dc Resistance At 25 Deg Celsius:

1000000.0 megohms

Insulation Dc Resistance At Max Operating Temp:

100000.0 megohms

Mounting Facility Type And Quantity:

1 threaded bushing

Thready Qty Per Inch (tpi):

64

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Thread Size:

0.234 inches

Capacitance Range In Picofarads:

+0.8/+10.0 single section

Nonderated Voltage Rating And Type:

250.0 dc continuous single section

Adjustment Device Drive Type And Quantity:

1 slotted screw

Capacitance Drift In Picofarads:

0.02 single section

Special Features:

Body and supplied hardware shall be tin plated per mil-t-10727; type 1

Material:

Ceramic base

Terminal Type And Quantity:

1 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0