## NSN 5910-01-137-0152

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-137-0152

View Online at https://aerobasegroup.com/nsn/5910-01-137-0152				
Body Style:				
W/thd bushing mtg, terminals on opposite ends				
Reliability Indicator:				
Not established				
Terminal Length:				
0.281 inches				
Body Diameter:				
0.562 inches				
Body Length:				
1.062 inches				
Schematic Diagram Designator:				
Feedthrough				
Mounting Facility Screw Thread Series Designator:				
Unf				
Mounting Facility Type And Quantity:				
1 threaded bushing				
Features Provided:				
Hermetically sealed case				
Insulation Resistance At Maximum Operating Temp:				
5.0 megohm-microfarads				
Capacitance Value Per Section:				
0.680 microfarads single section				
Nonderated Operating Temp:				
Between -55.0 degrees celsius and 125.0 degrees celsius				
Thread Size:				
0.312 inches				
Nonderated Continuous Voltage Rating And Type Per Section:				
200.0 dc single section				
Tolerance Range Per Section:				
-20.00/+20.00 percent single section				
Case Material:				
Metal				
Insulation Resistance At Reference Temp:				
2000.0 megohm-microfarads				
Dissipation Factor At Reference Tempurature In Percent:				
1.5000				
Terminal Surface Treatment:				
Solder				
Terminal Type And Quantity:				
2 tab, solder lug				
Shelf Life:				

N/a

## NSN 5910-01-137-0152

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



	nit	O+	Measure:
u		v	wicasuic.

--

Demilitarization:

No

Fiig:

A010b0