

View Online at <https://aerobasegroup.com/nsn/5910-01-137-4211>

**Body Style:**

W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals

**Reliability Indicator:**

Establishedestablishedestablished

**Reliability Failure Rate Level In Percent:**

1.00001.00001.0000

**Terminal Length:**

1.500 inches 1.500 inches 1.500 inches

**Body Diameter:**

0.383 inches

**Body Length:**

1.578 inches

**Terminal Diameter:**

0.032 inches

**Schematic Diagram Designator:**

Electrod (s) grounded to case, w/gnd terminal

**Impedance At Minimum Operating Tempurature In Ohms:**

154.0

**Electrical Polarization:**

Polarized

**Capacitance Value Per Section:**

12.000 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Dc Leakage At Maximum Operating Temp:**

48.0 microamperes

**Nonderated Continuous Voltage Rating And Type Per Section:**

200.0 dc single section

**Tolerance Range Per Section:**

-10.00/+30.00 percent single section

**Case Material:**

Metal

**Capacitive Electrode Material:**

Aluminum

**Equivalent Series Resistance At Reference Tempurature In Ohms:**

11.05

**Dc Leakage At Reference Temp:**

8.000 microamperes

**Terminal Surface Treatment:**

Solder

**Case Insulation Material:**

Plastic

**Test Data Document:**

81349-mil-c-39018 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Specification Data:**

81349-mil-c-39018/1 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A010b0