Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-137-6342

### Body Style:

W/o mtg facilities terminal (s) on one surface

**Reliability Indicator:** 

Not established

## **Terminal Length:**

0.500 inches

#### **Body Length:**

0.420 inches

#### **Body Width:**

0.298 inches

#### **Body Height:**

0.160 inches

#### Center To Center Distance Between Terminals Parallel To Length:

0.300 inches

#### **Terminal Diameter:**

0.025 inches

### Schematic Diagram Designator:

No common or grounded electrode (s)

#### **Capacitance Value Per Section:**

0.010 microfarads single section

### Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

#### **Tolerance Range Per Section:**

-2.00/+2.00 percent single section

#### **Case Material:**

Plastic

## Insulation Resistance At Reference Temp:

50000.0 megohms

# Dissipation Factor At Reference Tempurature In Percent:

0.5000

# **Terminal Surface Treatment:**

Solder

# Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

No



**Fiig:** A010b0