NSN 5910-01-138-6997

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-138-6997

| view Online at https://aerobasegroup.com/nsn/5910-01-138-6997 |
|---|
| Body Style: |
| W/o mtg facilities, axial terminals |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| Between 1.625 inches and 1.750 inches |
| Body Diameter: |
| 0.400 inches |
| Body Length: |
| 1.120 inches |
| Terminal Diameter: |
| 0.025 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Insulation Resistance At Maximum Operating Temp: |
| 250.0 megohm-microfarads |
| Capacitance Value Per Section: |
| 2.000 microfarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 125.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 75.0 dc single section |
| Tolerance Range Per Section: |
| -10.00/+10.00 percent single section |
| Case Material: |
| Metal |
| Insulation Resistance At Reference Temp: |
| 50000.0 megohm-microfarads |
| Dissipation Factor At Reference Tempurature In Percent: |
| 0.500 |
| Terminal Surface Treatment: |
| Solder |
| Dielectric Material: |
| Plastic polycarbonate |
| Case Insulation Material: |
| Plastic |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

--

NSN 5910-01-138-6997

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



| _ | | •• | • • | | | | |
|----|----|----|-----|-----|-----|---|----|
| וו | em | ш | 112 | rız | 211 | n | ٠. |
| | | | | | | | |

No

Fiig:

A010b0