NSN 5910-01-138-9575

Electrolytic Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-138-9575

| Body Style: |
|---|
| W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals |
| Reliability Indicator: |
| Not establishednot established |
| Terminal Length: |
| 1.500 inches 1.500 inches 1.500 inches |
| Body Diameter: |
| 0.500 inches |
| Body Length: |
| 1.562 inches |
| Terminal Diameter: |
| 0.025 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Electrical Polarization: |
| Polarized |
| Capacitance Value Per Section: |
| 12.000 microfarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 85.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 350.0 dc single section |
| Tolerance Range Per Section: |
| -10.00/+50.00 percent single section |
| Case Material: |
| Metal |
| Capacitive Electrode Material: |
| Aluminum |
| Terminal Surface Treatment: |
| Solder |
| Case Insulation Material: |
| Plastic |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiia: |

A010b0