NSN 5910-01-139-1201

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-139-1201 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Not established **Terminal Length:** 25.4 millimeters **Body Diameter:** 3.8 millimeters **Body Length:** 8.0 millimeters **Terminal Diameter:** 0.8 millimeters **Schematic Diagram Designator:** No common or grounded electrode (s) **Internal Electrical Connection Type:** Extended foil **Features Provided:** Hermetically sealed case **Insulation Resistance At Maximum Operating Temp:** 250.0 megohms **Capacitance Value Per Section:** 10.000 picofarads single section **Nonderated Operating Temp:** Between -65.0 degrees celsius and 125.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -150.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 350.0 dc single section **Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:** -80.0/+80.0 single section **Tolerance Range Per Section:** -2.00/+2.00 picofarads single section **Case Material:** Metal **Insulation Resistance At Reference Temp:** 25000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 0.500 **Terminal Surface Treatment:** Solder

Dielectric Material:

Plastic polystyrene

NSN 5910-01-139-1201

Plastic Dielectric Fixed Capacitor - Page 2 of 2



| Case Insulation Material: |
|-----------------------------|
| Plastic |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A010b0