## NSN 5910-01-139-3006

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-139-3006

Body	Styl	۵.
Doug	JLY	œ.

W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals

**Reliability Indicator:** 

Not establishednot established

**Terminal Length:** 

Between 1.250 inches and 1.250 inches and 1.750 inches 1.750 inches

**Body Diameter:** 

0.289 inches

**Body Length:** 

0.686 inches

**Terminal Diameter:** 

0.025 inches

**Schematic Diagram Designator:** 

Electrod (s) grounded to case, w/gnd terminal

**Anode Type:** 

Solid

**Electrical Polarization:** 

Polarized

**Features Provided:** 

Hermetically sealed case

**Capacitance Value Per Section:** 

150.000 microfarads single section

**Nonderated Operating Temp:** 

Between -80.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

20.0 dc single section

**Tolerance Range Per Section:** 

-20.00/+20.00 percent single section

Case Material:

Metal

**Capacitive Electrode Material:** 

Tantalum

**Dissipation Factor At Reference Tempurature In Percent:** 

8.000

Dc Leakage At Reference Temp:

12.000 microamperes

**Terminal Surface Treatment:** 

Solder

**Case Insulation Material:** 

Plastic

**Terminal Type And Quantity:** 

2 uninsulated wire lead

## NSN 5910-01-139-3006

Electrolytic Fixed Capacitor - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0