Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-141-4516

Body Style:
Chip type
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
1.0000
Terminal Length:
0.015 inches
Body Length:
0.110 inches
Body Width:
0.110 inches
Body Height:
Between 0.058 inches and 0.102 inches
Center To Center Distance Between Terminals Parallel To Length:
0.080 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Insulation Resistance At Maximum Operating Temp:
100000.0 megohms
Capacitance Value Per Section:
100.000 picofarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
90.0 single section
Nonderated Continuous Voltage Rating And Type Per Section:
500.0 dc single section
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Tolerance Range Per Section:
-1.00/+1.00 percent single section
Case Material:
Ceramic or glass
Insulation Resistance At Reference Temp:
1000000.0 megohms
Dissipation Factor At Reference Tempurature In Percent:
0.0500
Quality Factor At Reference Temp:
3200.0000
Terminal Surface Treatment:
Silver or palladium



## **Precious Material And Location:**

Terminal surfaces palladium and terminal surfaces silver

# **Test Data Document:**

81349-mil-c-55681 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

2 bonding pad

### **Specification Data:**

81349-mil-c-55681/4 government specification

Shelf Life:

N/a

Unit Of Measure:

---

# Demilitarization:

No

#### Fiig:

A010b0