NSN 5910-01-142-1236

Electrolytic Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-142-1236

| Body Style: |
|---|
| $W\!/o\ mtg\ facilities,\ axial\ terminals w\!/o\ mtg\ facilities,\ axial\ terminals$ |
| Reliability Indicator: |
| Not establishednot established |
| Terminal Length: |
| 1.500 inches 1.500 inches 1.500 inches |
| Body Diameter: |
| 0.135 inches |
| Body Length: |
| 0.286 inches |
| Terminal Diameter: |
| 0.020 inches |
| Schematic Diagram Designator: |
| Electrod (s) grounded to case, w/gnd terminal |
| Electrical Polarization: |
| Polarized |
| Capacitance Value Per Section: |
| 2.200 microfarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 85.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 20.0 dc single section |
| Tolerance Range Per Section: |
| -10.00/+10.00 percent single section |
| Case Material: |
| Metal |
| Capacitive Electrode Material: |
| Tantalum |
| Terminal Surface Treatment: |
| Solder |
| Case Insulation Material: |
| Plastic |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A010b0