NSN 5910-01-142-1623

Ceramic Dielectric Variable Capacitor - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5910-01-142-1623 |
|---|
| Body Style: |
| Rotary |
| Body Diameter: |
| 0.375 inches |
| Body Height: |
| 0.410 inches |
| Center To Center Distance Between Terminals Parallel To Diameter: |
| 0.299 inches |
| Inclosure Type: |
| Encased |
| Terminal Location: |
| Circumference bent forward |
| Adjustment Device Torque: |
| Between 2.170 inch-ounces and 6.210 inch-ounces |
| Insulation Dc Resistance At 25 Deg Celsius: |
| 10.0 gigohms |
| Mounting Facility Type And Quantity: |
| 3 terminal |
| Nonderated Operating Temp: |
| Between -40.0 degrees celsius and 85.0 degrees celsius |
| Capacitance Range In Picofarads: |
| +3.0/+10.0 single section |
| Nonderated Voltage Rating And Type: |
| 175.0 ac peak single section or 250.0 dc continuous single section |
| Capacitance Change In Percent At Operating Tempurature From 25 Deg Celsius: |
| -4.50/+2.00 single section and -2.50/+2.00 single section |
| Adjustment Device Drive Type And Quantity: |
| 1 slotted screw |
| Terminal Type And Quantity: |
| 3 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A096a0 |