

View Online at <https://aerobasegroup.com/nsn/5910-01-142-3372>

Body Style:

W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals

Mil-std-1276 Wire Lead Type Designator:

N-2n-2n-2n-2

Reliability Indicator:

Not establishednot establishednot establishednot established

Terminal Length:

2.250 inches 2.250 inches 2.250 inches 2.250 inches

Body Diameter:

0.296 inches

Body Length:

0.734 inches

Terminal Diameter:

Between 0.024 inches and 0.030 inches

Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

Impedance At Minimum Operating Tempurature In Ohms:

200.0

Electrical Polarization:

Polarized

Capacitance Value Per Section:

11.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Dc Leakage At Maximum Operating Temp:

2.0 microamperes

Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

Tolerance Range Per Section:

-20.00/+20.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Tantalum

Equivalent Series Resistance At Reference Tempurature In Ohms:

3.00

Dc Leakage At Reference Temp:

0.500 microamperes

Case Insulation Material:

Plastic

Precious Material And Location:

Terminal surfaces gold

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0