

View Online at <https://aerobasegroup.com/nsn/5910-01-143-4661>

**Body Style:**

W/thd bushing mtg, terminals on opposite ends

**Reliability Indicator:**

Not established

**Terminal Length:**

0.170 inches

**Body Diameter:**

0.375 inches

**Body Length:**

0.610 inches

**Schematic Diagram Designator:**

Feedthrough

**End Application:**

Spruance class dd (963), arleigh burke class ddg, ticonderoga class cg (47), oliver perry class ddg, kidd class dd. Sh-60b lamps mark iii helicopter. An/sqr-4 radio terminal set.

**Mounting Facility Screw Thread Series Designator:**

Unf

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Capacitance Value Per Section:**

0.375 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Thread Size:**

0.250 inches

**Nonderated Continuous Voltage Rating And Type Per Section:**

200.0 dc single section

**Criticality Code Justification:**

Feat

**Tolerance Range Per Section:**

+0.30/+0.67 microfarads single section

**Case Material:**

Metal

**Insulation Resistance At Reference Temp:**

1300.0 megohms

**Special Features:**

Weapon system essential

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0