

View Online at <https://aerobasegroup.com/nsn/5910-01-143-4661>

Body Style:

W/thd bushing mtg, terminals on opposite ends

Reliability Indicator:

Not established

Terminal Length:

0.170 inches

Body Diameter:

0.375 inches

Body Length:

0.610 inches

Schematic Diagram Designator:

Feedthrough

End Application:

Spruance class dd (963), arleigh burke class ddg, ticonderoga class cg (47), oliver perry class ddg, kidd class dd. Sh-60b lamps mark iii helicopter. An/sqr-4 radio terminal set.

Mounting Facility Screw Thread Series Designator:

Unf

Mounting Facility Type And Quantity:

1 threaded bushing

Capacitance Value Per Section:

0.375 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Thread Size:

0.250 inches

Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

Criticality Code Justification:

Feat

Tolerance Range Per Section:

+0.30/+0.67 microfarads single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

1300.0 megohms

Special Features:

Weapon system essential

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0