NSN 5910-01-143-4670

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-143-4670

| Body Style: |
|---|
| W/o mtg facilities, terminal (s) on one endw/o mtg facilities, terminal(s) on one endw/o mtg facilities, terminal(s) on one end |
| Reliability Indicator: |
| Not establishednot established |
| Terminal Length: |
| 1.181 inches 1.181 inches 1.181 inches |
| Body Diameter: |
| 0.268 inches |
| Body Length: |
| 0.610 inches |
| Center To Center Distance Between Terminals Parallel To Diameter: |
| 0.197 inches |
| Terminal Diameter: |
| 0.024 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Electrical Polarization: |
| Polarized |
| Capacitance Value Per Section: |
| 33.000 microfarads single section |
| Nonderated Operating Temp: |
| Between -40.0 degrees celsius and 85.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 16.0 dc single section |
| Tolerance Range Per Section: |
| -20.00/+20.00 percent single section |
| Case Material: |
| Metal |
| Capacitive Electrode Material: |
| Aluminum |
| Terminal Surface Treatment: |
| Solder |
| Case Insulation Material: |
| Plastic |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

No

Demilitarization:

NSN 5910-01-143-4670

Electrolytic Fixed Capacitor - Page 2 of 2



Fiig:

A010b0