NSN 5910-01-145-0066

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-145-0066 **Body Style:** W/o mtg facilities, terminal (s) on one end Reliability Indicator: Not established **Terminal Length:** 0.468 inches **Body Diameter:** 1.750 inches **Body Length:** 3.000 inches **Center To Center Distance Between Terminals Parallel To Diameter:** 0.812 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Capacitance Value Per Section:** 7.500 microfarads single section **Nonderated Operating Temp:** Between 5.0 degrees celsius and 75.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 220.0 ac-rms single section **Criticality Code Justification:** Zzzy **Tolerance Range Per Section:** -6.00/+6.00 percent single section **Case Material:** Metal **Dissipation Factor At Reference Tempurature In Percent:** 0.1000 **Terminal Surface Treatment:** Solder **Special Features:** Item must comply with requirements of defense supply center columbus production standard no. Lo3225 **Terminal Type And Quantity:** 2 tab, solder lug **Reference Number Differentiating Characteristics:** Reference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing and testing specifications available at the dla icp Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5910-01-145-0066

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Fiig:

A010b0