e 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-145-7927

Thread Class:
2a Da da Otalaa
Body Style:
Terminal Length:
0.100 inches
Bushing Diameter:
Between 0.387 inches and 0.390 inches
Overall Height:
3.470 inches
Bushing Length:
0.400 inches
Alternating Current Rating In Amps:
15.0
Body Height:
3.130 inches
Overall Diameter:
0.875 inches
Quality Factor At 25 Deg Celsius:
5000.0
Mounting Facility Screw Thread Series Designator:
Unef
Bushing Shape:
Round w/flat
Bushing Width:
Between 0.330 inches and 0.344 inches
Mounting Facility Type And Quantity:
2 threaded bushing
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Thread Size:
0.375 inches
Capacitance Range In Picofarads:
+1.5/+45.0 single section
Nonderated Voltage Rating And Type:
3000.0 ac peak single section
Adjustment Device Drive Type And Quantity:
1 threaded hole
Material:
Ceramic insulation supporting
Terminal Type And Quantity:
1 ferrule and 1 threaded stud

Gas Dielectric Variable Capacitor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0