## NSN 5910-01-146-1286

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-146-1286

## **Body Style:**

W/o mtg facilities, terminal (s) on one end

## **Reliability Indicator:**

Not established

## **Terminal Length:**

0.280 inches

#### **Body Diameter:**

Between 1.374 inches and 1.406 inches

#### **Body Length:**

Between 4.107 inches and 4.233 inches

## Center To Center Distance Between Terminals Parallel To Diameter:

0.500 inches

#### **Terminal Diameter:**

0.190 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

#### **Electrical Polarization:**

Polarized

## Capacitance Value Per Section:

22000.000 microfarads single section

## Nonderated Operating Temp:

Between -40.0 degrees celsius and 85.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

16.0 dc single section

## **Tolerance Range Per Section:**

-10.00/+75.00 percent single section

#### Case Material:

Metal

**Capacitive Electrode Material:** 

Aluminum

## **Dissipation Factor At Reference Tempurature In Percent:**

50.000

## Equivalent Series Resistance At Reference Tempurature In Ohms:

0.067

## Dc Leakage At Reference Temp:

6.000 microamperes

## **Case Insulation Material:**

Plastic

## **Terminal Type And Quantity:**

2 threaded hole

## Shelf Life:

N/a

# NSN 5910-01-146-1286

Electrolytic Fixed Capacitor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0