## NSN 5910-01-146-9053

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-146-9053

**Body Style:** 

W/o mtg facilities, axial terminals

**Reliability Indicator:** 

Established

Reliability Failure Rate Level In Percent:

0.0100

**Terminal Length:** 

1.625 inches

**Body Diameter:** 

Between 0.100 inches and 0.200 inches

**Body Length:** 

Between 0.350 inches and 0.450 inches

**Terminal Diameter:** 

Between 0.019 inches and 0.024 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**End Application:** 

Mod kit e/i fscm 37695

**Insulation Resistance At Maximum Operating Temp:** 

7000.0 megohms

**Capacitance Value Per Section:** 

100000.000 picofarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 125.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

**Tolerance Range Per Section:** 

-1.00/+1.00 percent single section

**Case Material:** 

Plastic

Insulation Resistance At Reference Temp:

500000.0 megohms

**Terminal Surface Treatment:** 

Solder

**Test Data Document:** 

81349-mil-c-55514 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:** 

2 uninsulated wire lead

**Specification Data:** 

81349-mil-c-55514/4 government specification

Shelf Life:

N/a

## NSN 5910-01-146-9053

Plastic Dielectric Fixed Capacitor - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0